

Cox Sales Company  
2035 Cook Drive  
Salem, Virginia 24153  
Phone: (540) 345-2636 FAX: (540) 342-8684

## TECHNICAL DATA SHEET

**PRODUCT DESIGNATION:** 7859

**PRODUCT FEATURES:** PRESSURE SENSITIVE ADHESIVE WITH EXCELLENT TACK AND COHESIVE STRENGTH. PERMANENT FINAL BOND TO MANY SUBSTRATES AND SURFACES.

**SUGGESTED USE:** HOT MELT PRESSURE SENSITIVE APPLICATIONS

## TYPICAL PROPERTIES

**TYPE:** POLYMER BLEND

**SOLIDS:** 100%

**F&DA STATUS:** 175.105

**WEIGHT PER GALLON:** 8.4

LBS

**COLOR:** AMBER

**ODOR:** LIGHT RESIN TYPE

**CLEAN WITH:** HEAT, SCRAPER, PARAFFIN WAX

**PH:** N/A

**FLAMMABILITY:** N/A

**EFFECT FROM FREEZING:** NONE

**STORAGE LIFE:** INDEFINITE

**THIN WITH:** HEAT

**VISCOSITY:** 1100 CPS @ 350°F

**SUGGESTED SURFACE PREPARATION:** ALL SURFACES SHOULD BE CLEAN AND DRY, FREE OF DUST, DIRT, GREASE AND ANY OTHER FOREIGN MATERIALS

- THIS PRODUCT IS HEAT STABLE FOR 100 HOURS @ 350°F
- SUGGESTED APPLICATION TEMPERATURE RANGE: 280-330°F

**METHOD OF APPLICATION:** CONVENTIONAL HOT MELT EQUIPMENT

